


TECHNICAL DATA SHEET				
FLOORPAN FIX		7 MM - CLASS 31 - AC3		
THICKNESS	mm	7	EN 13329+A1	
WIDTH	mm	197	EN 13329+A1	
LENGHT	mm	1205	EN 13329+A1	
SURFACE		Authentic		
EUROPEAN STANDARD	-		EN13329	
PACKAGE THE DETAILS				
PIECE	12 piece / 1 package			
M ²	2,849 m ²			
KG	17 kg			
PALLET THE DETAILS				
PIECE	60 package / 1 pallet			
M ²	170,94 m ²			
KG	1060 kg			
CLASS	-	31	EN 13329+A1	
ABRASION RESISTANCE	-	AC3	EN 13329+A1	
THICKNESS SWELLING	%	≤18	ISO 24336	
RESISTANCE TO IMPACT	SMALL BALL	N	≥8	EN 13329+A1
	LARGE BALL	mm	≥500	EN 13329+A1
WARRANTY DOMESTIC / COMMERCIAL	Years	10/5	-	
RESISTANCE TO STAINING	-	Min. 5 (group 1 and 2) Min. 4 (group 3)	EN 438	
SURCAFE SOUNDNESS	N/mm ²	≥1.0	EN 13329+A1	
LOCK STRENGTH	LENGHT	kN/m	-	ISO 24334
	WIDTH	kN/m	-	
EFFECT OF A CASTOR CHAIR	25,000 Cycles	No Damage	EN 425:2002	
EFFECT OF A FURNITURE LEG	-	No Damage	EN 424	
OPENING BETWEEN ELEMENTS	mm	≤0,20	EN 13329+A1	
HEIGHT DIFFIRENCE BETWEEN ELEMENTS	mm	≤0,15	EN 13329+A1	
MOISTURE CONTENT	%	4-10	EN 322	
FIRE RESISTANCE	Class	C _s S1	EN 9239-1	
FORMALDEHYDE EMISSION	mg/m ² h	≤3,5 (E1)	EN 12460-3	



The mark of responsible forestry



Our products can also be produced with FSC and CARB certification upon request.